

ISUZU 'FORWARD' F120.240(E)

11.99T GVW

(Easyshift transmission) 4x2 rigid





EURO VI

×	
610-	

UK Standard vehicle plated weights (kg) GVW 11990 GTW 15490 UK Axle design weights (kg) Front

ISUZU

Rear

Weights (kg)					
Cab type		day	day	day	day
Wheelbase	WB	3790	4990	4990	5320
Rear Suspension		Steel	Steel	Air	Air
Vehicle Mass Unladen	Front	2599	2669	2689	2694
	Rear	1469	1514	1559	1559
Total		4068	4183	4248	4253
GVW		11990	11990	11990	11990
Max. Permissible Trailer Weight		3500	3500	3500	3500
Body & Payload Allowance		7922	7807	7742	7737

Dimensions (mm)					
Overall Length	OAL	6610	8380	8380	8685
Overhang - Front	FOH	1170	1170	1170	1170
Overhang - Rear	ROH	1645	2215	2215	2195
Cab Gap	СВ	150	150	150	150
C/L Front Axle to Rear of Cab	CA	556	556	556	556
Recommended Body Length	BL	5100	6800	6800	7300
Chassis Frame Width		840	840	840	840
Recommended Body Width		2550	2550	2550	2550
Recommended Maximum Body Width		2600*	2600*	2600*	2600*
Cab Width	OW	2200	2200	2200	2200
Overall Height (Unladen)	ОН	2585	2585	2585	2585
Chassis Height (Unladen)	EH	785	785	785	785
Minimum Road Clearance	HH	185	185	185	185
Track - Front	AW	1805	1805	1805	1805
Track - Rear	CW	1705	1705	1705	1705
Rear Axle Width	BW	2240	2240	2240	2240

*Max dimension for refrigerated bodies only

- Unladen weights excludes driver, fuel, Ad Blue. Includes spare wheel + carrier (Tolerance ± 3%).
 Body lengths are given as a guide only. Bodybuilders are responsible for ensuring all legal requirements are met.
 Maximum body lengths are calculated to remain within the maximum permitted overhang in the UK of 60% of the wheelbase. Cab gaps may vary.
 Isuzu Truck (UK) Ltd. shall have no liability whatsoever should the information supplied have incorrect data, descriptions or illustrations.



F120.240(E) 11.99T

ISUZU 'FORWARD' F120.240(E)

11.99T GVW

(Easyshift transmission) 4x2 rigid

Mechanical Specification (standard equipment)

Engine 4HK1TCH

Isuzu 2-stage turbo intercooled OHC 4 cylinder diesel (Euro VI) Bore: 115mm Stroke: 125mm Capacity: 5193cc Max Power: 177kW (240 PS) at 2600rpm Max Torque: 765Nm at 1600rpm Injection Type: Common rail Euro VI Compliance: EGR (Exhaust Gas Recirculation) with DPD (Diesel Particulate Diffuser) SCR Adblue and OBD

Fuel Tank

Capacity: 140 litres Ad Blue: 16 litres

Transmission

Electro hydraulic controlled 6-speed MZW6P with fully automated and sequential shift modes Ratios: 1st 6.615

2nd	4.095			
3rd	2.358			
4th	1.531			
5th	1.000			
6th	0.722			
reverse	6.615			
Rear Axle Ratio:	4.555:1			
Tyres: 245/70R 19.5 radial				
Wheels: Steel 19.5 x 6.75,				
8-stud				

Cab Exterior

Aerodynamic Isuzu Hexapod design white all steel with roof outline markers Tilt to 45 dea. Keyless door entry and immobiliser Laminated windscreen Non-slip entry steps 90 deg. opening doors Zinc galvanised frame structure 2 halogen headlamp units with indicators Front mudguards with spray suppression All-steel front bumper with fog and daytime running lamps

Chrome radiator grille Aluminium rear bumper

Frame

Parallel ladder type channel section, straight side rails with rivetless upper flange

Cooling

Tube and fin type radiator with fan and viscous clutch Frame mounted fuel cooler

Clutch

Fluid hydrokinetic coupling with lock-up clutch

Cab Interior

Flame-resistant interior trim Vinyl floor matting Dual long grab handles each side SRS airbags driver and passenger Header console storage Interior fluorescent lighting

Seats (all cloth)

Driver's adjustable airsuspended seat with head restraint and 3-point seat belt with pre-tensioner Rigid centre seat with 2-point seatbelt Rigid passenger seat with head restraint and 3-point seat belt pre-tensioner

Vision

Large door mounted heated mirrors Front underview mirror and kerb mirror Driver and passenger sun visors Deep cut side windows to reduce blind spots Electric windows with driver control and lock with indicators

Heating & Ventilation

4-Speed blower Multiple cab vents

Axles

Front: Reverse Elliott I-Beam

Rear: Banjo type, fully floating

Suspension

Front: Multi Taper-leaf steel springs Rear: Multi Taper-leaf steel springs with helper, or Isuzu 4-bag if air

Steering

Recirculating ball type with full integral hydraulic power assistance Tilt and telescopic steering column

Brakes

System: ABS air over hydraulic, dual circuit with anti-slip regulation, Front: Drum 370mm x 150mm Rear: Drum 370mm x 150mm Park: Rear Wheel Air dryer

Instruments

Rev counter Tachograph, digital Siemens VDO Speedometer with odometer and trip Multi-information display provides data on servicing emissions and fuel economy Gauges: Fuel level, coolant temperature and air pressure Gear shift indicator display

Switches & Electrical

Electrical vehicle speed limiter set at 56mph (90kph) with automatic cruise control Steering column mounted switch for indicators, side lights, headlights, high beam, front and rear fog lamps Wiper and washer (2-speed and intermittent) Exhaust brake Brake warning buzzer Steering wheel horn Hazard lights Headlamp levelling Interior light Key operation for quick

EURO VI

cold start, start and stop Cigarette lighter Gearbox engage drive fast/ slow Central locking Reverse warning DPD engage Engine idle control Gearbox emergency overide Heated mirrors Engine guick warm-up ASR off Heater stage

Warning /Indicator Lamps

Battery charge Oil pressure Brake system I ow fuel Glow plug operation High beam indicators Parking brake on Exhaust brake operation Fuel/water separator Check engine ABS SVS **DPD** operation OBD Front and rear fog Air pressure warning 1st gear indicator Eco mode Engine over heat Adblue level Seat belt SRS air bag Easyshift warning

Tool Kit

Jack with a small selection of hand tools

Radio Radio with CD player

Storage Space


Centre seat back compartment Door pockets Twin overhead lockers Centre trav Dashboard pockets Card holder

Ancillaries

Starter: 24 V x 5.0kW Alternator: 24 V - 90 Amp Quick Start: 4 glow plugs on start relay Battery: 2 x 12 V - 115 AH

F120.240(E) 11.99T





The following optional items are available:

- Isuzu Branded Mats
- Aerodynamic Body Kits
- Satellite Navigation
- Reversing Aids
- PTO Switch
- Telematics

